



SJ-20i

Machine Specifications

機械規格	SJ-20i	
床面旋徑 Swing over bed	mm	400
滑座旋徑 Over cross slide	mm	200
最大加工直徑 Max. turning dia.	mm	100
最大加工長度 Max. work length	mm	330
夾頭尺寸 Chuck size	inch	6
X 軸行程 X axis travel	mm	360
Z 軸行程 Z axis travel	mm	350
主軸最高轉速 Spindle speed range	rpm	6000
主軸鼻端 Spindle nose	ASA	A2-5/A2-6
主軸通孔 Through spindle hole dia	mm	51/61
拉管內徑 Draw tube dia	mm	45/52
主軸前軸承內徑 Front bearing dia	mm	80/100
快速位移 Rapid traverse rate	m/min	X 30/Z30
刀具容量 No. of tool positions		4
主軸馬達 Spindle drive motor	kw	9/12
X 軸馬達 X axis motor	kw	2.29
Z 軸馬達 Z axis motor	kw	2.29
電力需求 Electrical power supply	kva	32
冷卻水箱容量 Coolant tank capacity	L	125
佔地面積 Floor space	mm	1800x1450
淨重 Net weight	kg	3000

※All specifications designs are subject to change without noticed. 以上規格僅供參考，規格若有變更恕不另行通知
 ※Motors spec. shown in the table is for siemens 802DSL control. 馬達規格依西門子控制器802DSL而設定

ECOCA[®]
 —Focus on every detail—

勝傑工業股份有限公司
 ECOCA INDUSTRIAL CO., LTD
 台灣台中市工業區28路401號

401, 28TH ROAD, TAICHUNG INDUSTRIAL PARK, TAICHUNG, TAIWAN.

TEL : +886-4-23597666 FAX : +886-4-23597669

http://www.ecoca.com E-mail : biz@ecoca.com